



SUGGESTED USES

- Hinges
- Chains
- Trailer fasteners
- Ball bearings
- Engine shaft

TECHNICAL SHEET

No. 616

FASLUB® RED GREASE ALUMINUM COMPLEX LUBRICANT

Lubricant Heat Resistant (-18°C to 200°C). FASLUB® Provides extra protection against pressure and washouts. Resists oxidation, acids, alkalies, salt and water.

FEATURES:

Easy to locate the point where the grease is applied. Outstanding performance in high temperature applications.

PACKAGING :

UPC Code	777954604867
Cans per case	12
Shipping weight per case	- Lbs.
Product weight	298 g.

DIRECTIONS :

Shake can well. Spray in the area to be treated and saturate. Use extension tube as needed. Invert can and spray to clean tip. Provides extra protection against pressure and washouts. Resists oxidation, acids, alkalies, salt and water.

PROPERTIES :

Physical state	Aerosol.
Appearance	Red.
Odor	Hydrocarbon.
Vapour pressure(psig)-aerosol @ 20 C	40-50.
Boiling point (°c)(conc)	62-255.
Evaporation rate	Less than 1
N-butyl acetate = 1	
Vapour density (air=1) By weight)	Greater than 1.
Solubility in water g/l (20°c)	Negligible.
Specific gravity (liquid)	0.74-0.78.
Aerosol percent volatile (By weight)	63-64.



6500, rue Zéphirin-Paquet,
Parc industriel Armand Viau
Québec (Québec) Canada G2C 0M3

1 800 463-5259
www.prdistribution.ca